



## SAFETY DATA SHEET

# Octamar™ BT-25

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name	:	Octamar™ BT-25
Product code	:	FS-000281
Internal code	:	FS-000281
Date of issue/ Date of revision	:	5/18/2023
Date of previous issue	:	4/3/2023
Version	:	5
Product type	:	Liquid.
Chemical identity	:	Not available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Petrochemical industry: Fuel additive.

#### 1.3 Details of the supplier of the safety data sheet

UK Supplier	:	Innospec Limited Innospec Manufacturing Park Oil Sites Road, Ellesmere Port Cheshire CH65 4EY United Kingdom
Telephone no.:	:	+44 (0)151 355 3611
Fax no.	:	+44 (0)151 356 2349

e-mail address of person responsible for this SDS	:	sdsinfo@innospecinc.com
EU Supplier	:	Innospec Limited Boite Postale 19, F-55300 St. Mihiel Han-sur-Meuse, Meuse, France + 33 3 2991 7300

#### 1.4 Emergency telephone number

Country information	Emergency telephone number	Location
Europe ( all countries, all languages )	:	+44 (0) 1235 239 670
Middle East, Africa ( Arabic, French, English , Portuguese, Farsi)	:	+44 (0) 1235 239 671
Asia Pacific ( all countries except China )	:	+65 3158 1074

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

China	:	400 120 6011	Beijing China
Brazil	:	+55 11 3197 5891	Brazil
Mexico	:	+52 555 004 8763	Mexico

For More Information Call: 816-415-3323 (Monday-Friday 8-4:30pm) Central Time  
In Case of Emergency Call: Velocity EHS 24hr Emergency Number 800-255-3924

**Country information** : **Emergency telephone number**

**USA** : **800 424 9300**

**Canada, Puerto Rico, Virgin Islands** : **+1 800 424 9300**

**In case of difficulty using the toll-free number, or for ships at sea, call** : **+1 703 527 3887**

See section 16.



Indicates information that has changed from previously issued version.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 2, H371

STOT SE 3, H336

Asp. Tox. 1, H304

Aquatic Chronic 2, H411

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word**

: Danger

**Hazard statements**

: H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H371 - May cause damage to organs.  
H411 - Toxic to aquatic life with long lasting effects.

**Supplemental label elements**

: Not applicable.

#### Precautionary statements

**General**

: Not applicable.

**Prevention**

: P280 - Wear protective gloves. Wear eye or face protection.  
P273 - Avoid release to the environment.  
P260 - Do not breathe vapour.  
P270 - Do not eat, drink or smoke when using this product.  
P264 - Wash thoroughly after handling.

## SECTION 2: Hazards identification

<b>Response</b>	: <p>P391 - Collect spillage.</p> <p>P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor.</p> <p>P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.</p> <p>P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.</p> <p>P362 + P364 - Take off contaminated clothing and wash it before reuse.</p> <p>P302 + P352 - IF ON SKIN: Wash with plenty of water.</p> <p>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 - If eye irritation persists: Get medical advice or attention.</p>
<b>Storage</b>	: <p>P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.</p>
<b>Disposal</b>	: <p>P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.</p>
<b>Hazardous ingredients</b>	: <p>Hydrocarbons C10, Aromatics, &lt;1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]; Camphor and Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics [Distillates (petroleum), hydrotreated light]</p>

### Special packaging requirements

<b>Containers to be fitted with child-resistant fastenings</b>	: <p>Not applicable.</p>
<b>Tactile warning of danger</b>	: <p>Not applicable.</p>
<b>2.3 Other hazards</b>	

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

**Other hazards which do not result in classification**

:
 

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	REACH #: 01-2119463583-34 EC: 918-811-1 CAS: 64742-94-5 Index: 649-424-00-3	≥10 - ≤25	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1] [2]
Camphor	REACH #: 01-2119966156-31 EC: 200-945-0 CAS: 76-22-2	≥10 - ≤23	Flam. Sol. 2, H228 Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 2, H371	ATE [Oral] = 500 mg/kg ATE [Inhalation (vapours)] = 11 mg/	[1]
Formaldehyde, polymer with nonylphenol	CAS: 9040-65-7	≥10 - ≤25	Skin Irrit. 2, H315	-	[1]
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light]	REACH #: 01-2119456620-43 EC: 926-141-6 CAS: 64742-47-8 Index: 649-422-00-2	≥10 - ≤25	Asp. Tox. 1, H304 EUH066	-	[1] [2]
Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent	REACH #: 01-2119463588-24 EC: 919-284-0	<10	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2,	-	[1] [2]

## SECTION 3: Composition/information on ingredients

naphtha (petroleum), heavy arom.]	CAS: 64742-94-5		H411 EUH066		
naphthalene	REACH #: Exempt EC: 202-049-5 CAS: 91-20-3 Index: 601-052-00-2	<1	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 490 mg/kg M [Acute] = 1 M [Chronic] = 1	[1] [2]
tricresylphosphate	REACH #: 01-2119531335-46 EC: 215-548-8 CAS: 1330-78-5	≤0.3	Acute Tox. 4, H302 Acute Tox. 4, H312 Repr. 2, H361 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1]
4-nonylphenol, branched	EC: 284-325-5 CAS: 84852-15-3 Index: 601-053-00-8	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Oral] = 1300 mg/kg M [Acute] = 10 M [Chronic] = 10	[1] [3]

### Additional CAS # used in National Inventories

Solvent naphtha (petroleum), heavy arom.	-	64742-94-5
Camphor	-	76-22-2
Formaldehyde, polymer with nonylphenol	-	9040-65-7
Distillates (petroleum), hydrotreated light	-	64742-47-8 [1174522-15-6]
Solvent naphtha (petroleum), heavy arom.	-	64742-94-5
naphthalene	-	91-20-3
tricresylphosphate	-	1330-78-5
4-nonylphenol, branched	-	84852-15-3

### Additional information

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

Our REACH (pre-) registrations DO NOT cover the following:

1. The manufacture of these products by our company outside the EU unless covered by the Only Representative provisions, and
2. The importation of these products into Europe by other companies. Re-importation by other companies is not covered by our (pre-) registrations

Customers and other third parties importing and/or re-importing our products into Europe will need either:

- Their own (pre-) registration for substances contained in the imported product, or constituent monomers (imported above 1 tonne per year and >2% by weight) in the case of imported polymers, or
- In the case of importation only, to make use of the "Only Representative" provisions, if available.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

## SECTION 4: First aid measures

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion** : Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Wash out mouth with water. Stop if the exposed person feels sick as vomiting may be dangerous. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : May cause damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation.

**Ingestion** : May cause damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## SECTION 4: First aid measures

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## SECTION 6: Accidental release measures

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

**Storage** : Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
Solvent naphtha (petroleum), heavy arom.	<b>Supplier/Manufacturer (Europe, 2015).</b> EU HSPA (RCP Aromatic solvents 180 - 215): 151 mg/m <sup>3</sup> 8 hours.
Camphor	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 19 mg/m <sup>3</sup> 15 minutes. STEL: 3 ppm 15 minutes. TWA: 2 ppm 8 hours. TWA: 13 mg/m <sup>3</sup> 8 hours.
Distillates (petroleum), hydrotreated light	<b>EU OEL (Europe, 2009).</b> Supplier's information Reciprocal Calculation Procedure (RCP) : 1200 mg/m <sup>3</sup> 8 hours.
Solvent naphtha (petroleum), heavy arom.	<b>Supplier/Manufacturer (Europe, 2015).</b> EU HSPA (RCP Aromatic solvents 180 - 215): 151 mg/m <sup>3</sup> 8 hours.
naphthalene	<b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b> TWA: 10 ppm 8 hours. TWA: 50 mg/m <sup>3</sup> , 0 times per shift, 8 hours.
1,2,4-trimethylbenzene	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> [trimethylbenzenes, all isomers or mixtures] TWA: 25 ppm 8 hours. TWA: 125 mg/m <sup>3</sup> 8 hours.
mesitylene	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> [trimethylbenzenes, all isomers or mixtures] TWA: 25 ppm, 0 times per shift, 8 hours. TWA: 125 mg/m <sup>3</sup> , 0 times per shift, 8 hours.
iron tris(2-ethylhexanoate)	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [iron salts]</b> STEL: 2 mg/m <sup>3</sup> , (as Fe) 15 minutes. TWA: 1 mg/m <sup>3</sup> , (as Fe) 8 hours.
triphenyl phosphate	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 6 mg/m <sup>3</sup> , 0 times per shift, 15 minutes. TWA: 3 mg/m <sup>3</sup> , 0 times per shift, 8 hours.
Reaction mass of ethylbenzene and xylene	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-,p- or mixed isomers] Absorbed through skin.</b> STEL: 441 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes.
maleic anhydride	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation sensitiser.</b> STEL: 3 mg/m <sup>3</sup> 15 minutes. TWA: 1 mg/m <sup>3</sup> 8 hours.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	DNEL	Long term Dermal	12.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	151 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	7.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	32 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Oral	7.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	2.1 mg/kg bw/day	General population	Systemic
	DMEL	Long term Inhalation	3.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	10.2 mg/m <sup>3</sup>	General population	Systemic
	DMEL	Long term Dermal	23.4 mg/kg bw/day	Workers	Systemic
	DMEL	Long term Dermal	42.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	4.3478 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	10 mg/kg bw/day	Workers	Systemic
Camphor	DNEL	Long term Inhalation	17.6316 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	12.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	151 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	7.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	32 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Oral	7.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	0.03 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.28 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.69 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.69 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.95 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.31 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	2.31 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Oral	25.6 mg/kg bw/day	General population	Systemic
Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent naphtha (petroleum), heavy arom.]	DNEL	Short term Inhalation	143.5 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	160.23 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	226 mg/m <sup>3</sup>	General	Systemic
	DNEL	Short term			

## SECTION 8: Exposure controls/personal protection

naphthalene	DNEL	Inhalation Short term	384 mg/m <sup>3</sup>	population Workers	Systemic
	DNEL	Inhalation Long term	3.57 mg/kg bw/day	Workers	Systemic
	DNEL	Long term	25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Long term	25 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Long term	3.57 mg/kg bw/day	Workers	Systemic
	DNEL	Long term	25 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Long term	25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term	0.05 mg/kg bw/day	General population	Systemic
	DNEL	Inhalation Long term	0.08 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term	0.46 mg/m <sup>3</sup>	Workers	Systemic
tricresylphosphate	DNEL	Inhalation Long term	1.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term	2.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	15 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Long term	1 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	7.5 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Long term	0.5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Dermal	7.6 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Inhalation Short term	0.8 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.4 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	3.8 mg/kg bw/day	General population [Consumers]	Systemic
4-nonylphenol, branched	DNEL	Inhalation Long term	0.4 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.08 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.08 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.4 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	0.5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Short term	0.8 mg/m <sup>3</sup>	General population Workers	Systemic
	DNEL	Inhalation Short term	1 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	3.8 mg/kg	General	Systemic

## SECTION 8: Exposure controls/personal protection

	DNEL	Long term Dermal	bw/day 7.5 mg/kg bw/day	population Workers	Systemic
	DNEL	Short term Dermal	7.6 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	15 mg/kg bw/day	Workers	Systemic

### PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
naphthalene	PNEC	Fresh water	2.4 µg/l	-
	PNEC	Marine	0.24 µg/l	-
	PNEC	Sewage Treatment Plant	2.9 mg/l	-
	PNEC	Fresh water sediment	67.2 µg/kg dwt	-
	PNEC	Marine water sediment	67.2 µg/kg dwt	-
	PNEC	Soil	53.3 µg/kg dwt	-
4-nonylphenol, branched	-	Fresh water	0.000614 mg/l	-
	-	Marine water	0.000527 mg/l	-
	-	Intermittent release	0.00017 mg/l	-
	-	Fresh water sediment	4.62 mg/kg dwt	-
	-	Marine water sediment	1.23 mg/kg dwt	-
	-	Sewage Treatment Plant	9.5 mg/l	-
	-	Soil	2.3 mg/kg dwt	-
	-	Secondary Poisoning	2.36 mg/kg	-

### 8.2 Exposure controls

#### **Appropriate engineering controls**

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Individual protection measures

##### **Hygiene measures**

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### **Eye/face protection**

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

##### **Skin protection**

###### **Hand protection**

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

###### **Body protection**

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

###### **Other skin protection**

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	: Liquid.						
<b>Colour</b>	: Brownish [Dark]						
<b>Odour</b>	: Characteristic.						
<b>Odour threshold</b>	: Not available.						
<b>pH</b>	: Not available.						
<b>Melting point/freezing point</b>	: Not available.						
<b>Initial boiling point and boiling range</b>	: Lowest known value: 178 to 215°C (352.4 to 419°F)(Solvent naphtha (petroleum), heavy arom.). Weighted average: 259.69°C (499.4°F)						
<b>Flash point</b>	: Closed cup: 66°C (150.8°F)						
<b>Evaporation rate</b>	: Highest known value: 0.05 (Solvent naphtha (petroleum), heavy arom.) Weighted average: 0.05 compared with butyl acetate						
<b>Flammability (solid, gas)</b>	: Not available.						
<b>Burning time</b>	: Not applicable.						
<b>Burning rate</b>	: Not applicable.						
<b>Upper/lower flammability or explosive limits</b>	: Greatest known range: Lower: 0.5% Upper: 8% (Distillates (petroleum), hydrotreated light)						
<b>Vapour pressure</b>	: Highest known value: 0.1 kPa (0.8 mm Hg) (at 20°C) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 0.09 kPa (0.68 mm Hg) (at 20°C)						
<b>Vapour density</b>	: Highest known value: 4.6 to 5.5 (Air = 1) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 3.87 (Air = 1)						
<b>Relative density</b>	: Not available.						
<b>Density</b>	: 0.9444 g/cm³ [15°C (59°F)]						
<b>Solubility(ies)</b>	:						
<table border="1"> <thead> <tr> <th>Media</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td>cold water</td> <td>Very slightly soluble</td> </tr> <tr> <td>hot water</td> <td>Very slightly soluble</td> </tr> </tbody> </table>		Media	Result	cold water	Very slightly soluble	hot water	Very slightly soluble
Media	Result						
cold water	Very slightly soluble						
hot water	Very slightly soluble						
<b>Miscible with water</b>	: No.						
<b>Partition coefficient: n-octanol/water</b>	: Not applicable.						
<b>Auto-ignition temperature</b>	: >400°C (>752°F)						
<b>Decomposition temperature</b>	: Not available.						
<b>Viscosity</b>	: Kinematic (40°C (104°F)): 17 mm²/s (17 cSt)						
<b>Explosive properties</b>	: Not available.						
<b>Oxidising properties</b>	: Not applicable.						
<b>Particle characteristics</b>							
<b>Median particle size</b>	: Not applicable.						

### 9.2 Other information

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Species	Result type	Dose
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	Rat	LC50 Inhalation Vapour	>590 mg/m <sup>3</sup>
Camphor	OECD 402 Acute Dermal Toxicity	Rabbit	LD50 Dermal	>2 mL/kg
	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LDLo Oral	5 mL/kg
	-	Rat	LD50 Dermal	>2000 mg/kg
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light]	OECD 423 Acute Oral toxicity - Acute Toxic Class Method	Mouse	LD50 Oral	1310 mg/kg
	OECD 403 Acute Inhalation Toxicity	Rat	LD50 Oral	>5000 mg/kg
	-	Rat	LC50 Inhalation Vapour	>5000 mg/m <sup>3</sup>
Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent naphtha (petroleum), heavy arom.]	OECD 402 Acute Dermal Toxicity	Rabbit	LD50 Dermal	>5000 mg/kg
	OECD 401 Acute Oral Toxicity	Rat	LD50 Oral	>5000 mg/kg
	-	Rat	LC50 Inhalation Vapour	>590 mg/m <sup>3</sup>
naphthalene	-	Rabbit	LD50 Dermal	>2 mL/kg
	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LDLo Oral	5 mL/kg
	-	Rat	LC50 Inhalation Vapour	>340 mg/m <sup>3</sup>
tricresylphosphate	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LD50 Oral	490 mg/kg
	-	Rabbit	LD50 Dermal	>10000 mg/kg
4-nonylphenol, branched	-	Rat	LD50 Oral	3 g/kg
	-	Rat	LD50 Oral	1300 mg/kg

#### Acute toxicity estimates (ATE)

## SECTION 11: Toxicological information

Route	ATE value
Oral Inhalation (vapours)	2482.42 mg/kg 54.61 mg/l

### Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	Mammal - species unspecified	Eyes - Mild irritant -
Camphor	OECD 437 Bovine Corneal Opacity and Permeability Test OECD 439 In Vitro Skin Irritation: Human Skin Model Test OECD 431 In Vitro Skin Corrosion: Human Skin Model Test	Rabbit Isolated bovine cornea Human	Skin - Mild irritant - Eyes - Severe irritant - Skin - Irritant -
Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent naphtha (petroleum), heavy arom.]	-	Mammal - species unspecified	Eyes - Mild irritant -
tricresylphosphate	-	Rabbit	Skin - Mild irritant -
4-nonylphenol, branched	-	Rabbit	Eyes - Mild irritant -
	-	Rabbit	Skin - Mild irritant -
	-	Rabbit	Eyes - Severe irritant -
	-	Rabbit	Skin - Severe irritant -

### Sensitisation

Product/ingredient name	Test	Species	Result
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light]	-	Rat	Not sensitizing -

### Mutagenicity

Product/ingredient name	Test	Experiment	Result
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light]	-	Experiment: In vivo Subject: Bacteria	Negative -

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation.

## SECTION 11: Toxicological information

**Ingestion** : May cause damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

No known significant effects or critical hazards.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Test	Species	Exposure	Result
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	Algae	72 hours	Acute EC50 1 to 3 mg/l
	-	Daphnia	48 hours	Acute EC50 3 to 10 mg/l
	-	Fish	96	Acute LC50 2 to 5 mg/l

## SECTION 12: Ecological information

Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent naphtha (petroleum), heavy arom.]	-	Algae	hours 72 hours	Acute EC50 1 to 3 mg/l
naphthalene	-	Daphnia	48 hours	Acute EC50 3 to 10 mg/l
	-	Fish	96 hours	Acute LC50 2 to 5 mg/l
	-	Daphnia - Water flea - Daphnia magna	48 hours	Acute EC50 1.96 mg/l
	-	Crustaceans - Daggerblade grass shrimp -	48 hours	Fresh water
	-	Palaemonetes pugio	96 hours	Acute LC50 2350 µg/l
	-	Fish - Oncorhynchus mykiss	3 weeks	Marine water
	-	Crustaceans - Fiddler crab - Uca pugnax - Adult	60 days	Acute LC50 1.6 mg/l
	-	Fish - Mozambique tilapia - Oreochromis mossambicus	96 hours	Chronic NOEC 0.5 mg/l
	-	Algae - Green algae - Scenedesmus pannonicus - Exponential growth phase	96 hours	Chronic NOEC 1.5 mg/l
	-	Daphnia - Daphnia magna	48 hours	Fresh water
	-	Fish - Oncorhynchus mykiss	96 hours	Acute EC50 3.2 mg/l
	-	Fish - Threespine stickleback - Gasterosteus aculeatus - Egg	96 hours	Acute LC50 0.26 mg/l
	-	Algae - Diatom - Skeletonema costatum	72 hours	Chronic NOEC 160 µg/l
	-	Algae - Diatom - Skeletonema costatum	96 hours	Fresh water
	-	Crustaceans - Amphipod - Eohaustorius estuarius - Adult	48 hours	Acute EC50 0.03 mg/l
	-	Algae - Diatom - Skeletonema costatum	96 hours	Marine water
	-	Crustaceans - Scud - Gammarus fossarum - Adult	21 days	Acute EC50 0.027 mg/l
	-	Fish - Fathead minnow - Pimephales promelas - Embryo	33 days	Marine water
				Chronic NOEC 5 µg/l
				Fresh water
				Chronic EC10 0.012 mg/l
				Marine water
				Chronic NOEC 7.4 µg/l
				Fresh water

## 12.2 Persistence and degradability

## SECTION 12: Ecological information

Product/ingredient name	Test	Result
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light] tricresylphosphate	OECD 301F Ready Biodegradability - Manometric Respirometry Test	69 % - Readily - 28 days
	OECD 301B Ready Biodegradability - CO <sub>2</sub> Evolution Test	82 % - 28 days
	OECD 301C Ready Biodegradability - Modified MITI Test (I)	80 % - 28 days

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	-	Inherent
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light]	-	-	Readily
Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent naphtha (petroleum), heavy arom.]	-	-	Inherent
tricresylphosphate	-	50%; < 28 day(s)	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	2.8 to 6.5	<100	low
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics [Distillates (petroleum), hydrotreated light]	6 to 8	-	high
Hydrocarbons, C10, aromatics, >1% naphthalene [Solvent naphtha (petroleum), heavy arom.]	-	<100	low
naphthalene 4-nonylphenol, branched	3.4 5.4	36.5 to 168 740	low high

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

## SECTION 12: Ecological information

### 12.6 Endocrine disrupting properties

No known significant effects or critical hazards.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### **Hazardous waste**

: The classification of the product may meet the criteria for a hazardous waste.



#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

#### **Special precautions**

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), heavy arom., Solvent naphtha (petroleum), heavy arom.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), heavy arom., Solvent naphtha (petroleum), heavy arom.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), heavy arom., Solvent naphtha (petroleum), heavy arom.). Marine pollutant (Solvent naphtha (petroleum), heavy arom., Solvent naphtha (petroleum), heavy arom.)	Environmentally hazardous substance, liquid, n.o.s. (Solvent naphtha (petroleum), heavy arom., Solvent naphtha (petroleum), heavy arom.)
14.3 Transport hazard class(es)	9  	9  	9  	9  
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

## SECTION 14: Transport information

<b>Additional information</b>	<p>This product is not regulated as a dangerous good when transported in sizes of <math>\leq 5</math> L or <math>\leq 5</math> kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.</p> <p><b>Hazard identification</b> number 90</p> <p><b>Limited quantity</b> 5 L</p> <p><b>Special provisions</b> 274, 335, 601, 375</p> <p><b>Tunnel code</b> (-)</p>	<p>This product is not regulated as a dangerous good when transported in sizes of <math>\leq 5</math> L or <math>\leq 5</math> kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.</p> <p><b>Special provisions</b> 274, 335, 375, 601</p>	<p>This product is not regulated as a dangerous good when transported in sizes of <math>\leq 5</math> L or <math>\leq 5</math> kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.</p> <p><b>Emergency schedules</b> F-A, S-F</p> <p><b>Special provisions</b> 274, 335, 969</p>	
<b>14.6 Special precautions for user</b>				
<b>14.7 Maritime transport in bulk according to IMO instruments</b>				

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Substance of equivalent concern for environment	4-nonylphenol, branched and linear substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof	Candidate	ED/169/2012	12/19/2012

**Annex XVII - Restrictions** : Not applicable.

**on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles**

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not available.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

## SECTION 15: Regulatory information

**Industrial emissions** : Not listed  
**(integrated pollution prevention and control) -**  
**Water**

### Seveso Directive - Reporting thresholds (in tonnes)

#### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200	500

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### National regulations

**Chemical Weapons** :Not listed

**Convention List Schedule I**

**Chemicals**

**Chemical Weapons** :Not listed

**Convention List Schedule II**

**Chemicals**

**Chemical Weapons** :Not listed

**Convention List Schedule III**

**Chemicals**

### International lists

**Australia inventory (AIIIC)** :All components are listed or exempted.

**Canada inventory** :All components are listed or exempted.

**China inventory (IECSC)** :All components are listed or exempted.

**EU REACH Status** :Please contact your supplier for information on the REACH status of this material.

**Japan inventory** :All components are listed or exempted.

**Korea REACH Status** :Please contact your supplier for information on the REACH status of this material.

**New Zealand Inventory of Chemicals (NZIoC)** :All components are listed or exempted.

**Philippines inventory (PICCS)** :All components are listed or exempted.

**Taiwan REACH Status** :Please contact your supplier for information on the REACH status of this material.

**Turkey REACH Status** :Please contact your supplier for information on the REACH status of this material.

**United States inventory (TSCA 8b)** :All components are listed or exempted.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

Not to be used for hydraulic fracking applications

## SECTION 15: Regulatory information

## SECTION 16: Other information

<b>Abbreviations and acronyms</b>	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
-----------------------------------	---

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 2, H371	Calculation method
STOT SE 3, H336	Calculation method
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 2, H411	Calculation method

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H228 Flammable solid. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H371 May cause damage to organs. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. EUH071 Corrosive to the respiratory tract.
--	---

<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 4 ACUTE TOXICITY - Category 4 Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
---	---

**SECTION 16: Other information**

Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Sol. 2	FLAMMABLE SOLIDS - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 2	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of printing** : 2023-05-18**Date of issue/ Date of revision** : 5/18/2023**Date of previous issue** : 5/18/2023**Version** : 5**Emergency contact numbers for local language support in Asia Pacific region**

Country information	Languages supported	Telephone no.:	Location
Australia	English	+61 2 8014 4558	Australia
Bangladesh	Bengali, English	+65 3158 1200	Singapore
China	Mandarin, English	400 120 6011	Beijing China
India	Hindi, English	+65 3158 1198	Singapore
India ( local toll free number )	Hindi, English	000800 100 7479	India
Indonesia (local toll free number)	Bahasa Indonesian, English	00780 3011 0293	Indonesia
Japan	Japanese, English	+81 3 4578 9341	Japan
Korea	Korean, English	+65 3158 1285	Singapore
Malaysia	Bahasa Malaysian, English	+60 3 6207 4347	Malaysia
New Zealand	English	+64 9929 1483	New Zealand
Pakistan	Urdu, English	+65 3158 1329	Singapore
Philippines	Tagalog, English	+63 2 8231 2149	Singapore
Sri Lanka	Sinhalese, English	+65 3158 1195	Singapore
Thailand (local toll free number)	Thai, English	001800 1 2066 6751	Thailand
Vietnam	Vietnamese, English	+65 3158 1255	Singapore

**Notice to reader**

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

## **SECTION 16: Other information**